

PNEUTEK HIGH RISE LIFT

Optional lifting arms



The **Pneutek High Rise** lift is sturdy, strong and practical to use. Designed to accommodate all vehicles from small passenger to large SUV and 4X4. Improves operator conditions when working on the wheels. An essential tool for all tyre professionals.

The lifting strength (2700 kg)

Generated by an air spring that allows high capacity with limited pressure (maximum capacity achievable with only 7 BAR).

The heavy duty constructed full deck allows lifting at strategic points from all sides of the lift.

Optional lifting arms with three sets of lifting blocks ensure raising the vehicle from manufactures jacking points.

Specifications

Maximum capacity 2700 kg
Minimum height 115 mm
Maximum height 500 mm without arms
Operating pressure 7 bar
Weight 520 kg complete with arms
Platform width 2000mm
Platform length 1350mm
Platform length with arms extended 2300mm
Length of lifting arms 600mm
Length of drive on ramps 1200mm
Width of drive on ramps 500mm

Available in **Red, Yellow or Blue**

The **two-stage configuration of the approach ramps** allows lifting any vehicle, sports with low spoiler included, without touching the platform.

• **A mechanical safety device** prevents the risks of accidental vehicle falling in the event of an air pipeline breakage.

• **A relief valve calibrated** at 7 BAR limits the pressure inside the air spring to the prescribed values, relieving any excess to the atmosphere.

Optional accessories:

- Set of 4 adjustable revolving arms
- Set of 4 high pads 125mm
- Set of 4 mid pads 75mm
- Set of 4 low pads 50mm
- Set of 4 rubber blocks

Lifting pads are adjustable to any point of the lifting arms giving access to exact manufactures jacking points of the vehicle

**BIG TO SMALL
WE LIFT THEM
ALL**